



Technical Data:
MINERAL SPIRITS NE

Box 2219, Columbus, Ohio 43216 - (614) 790-3333

MINERAL SPIRITS NE

	<u>SPECIFICATIONS</u>	<u>TYPICAL*</u>
Specific Gravity at 60°F (D-891)(D-4052)	0.754 - 0.802	
Color, Saybolt (D-156)	+28 min	+30
Flash Point, °F, T.C.C. (D-56)	103 min	34-40
Kauri-Butanol Value (D-1133)		
Sulfur H ₂ S/Doctor (D-235)(D-4952)	Negative	
Corrosion (D-130)	1 max	
Composition, Volume % Aromatics	8 - 22	
Distillation, °F (D-86)		
IBP	300 min (148.9°C)	
Dry Point	415 max (212.8°C)	

ASHLAND® Mineral Spirits NE meets the following standard specifications:

ASTM D-235, Type I, Class A

Code: 86037 (BULK)

*Typical values should not be construed as a guaranteed analysis of any specific lot.

() Indicates ASTM Test Method

© Copyright 2009, Ashland Inc.

® Registered trademark, Ashland Inc.

0901

NOTICE: Ashland makes no warranty or representation as to the suitability of the product as specified herein for any particular application. The determination of the suitability of the above specification for any particular use is solely the responsibility of the user.

All precautionary labels and notices should be read and understood by all supervisory personnel and employees before using. Consult Ashland Distribution Company and OSHA regulations for additional safety and health information. Purchaser is responsible for complying with all applicable federal, state or local laws and regulations covering use of the product. Special attention should be given to consumer applications. Freedom to use any patent owned by Ashland or others is not to be inferred from any statement contained herein.