



Non Detergent Oils

Non Detergent Oils are compounded to provide good wear protection and resistance to oxidation, rust and foaming. They are not recommended for use in automotive gasoline applications built after 1963.

Features/Benefits:

- Good oxidation resistance
- Solid wear protection
- Excellent rust and corrosion protection
- Premium foam resistance

Applications/Specifications:

Non-Detergent Engine Oils are recommended for use in applications that specify a non-detergent oil. Non-Detergent Motor Oils may also be used for a GL-1 gear oil, hoist oil, air compressors and other industrial applications that require a non-detergent oils or as a general machine oil.

Typical Physical Specifications:					
SAE Grade	10w	20	30w	40w	50w
API Service Classification	SA	SA	SA	SA	SA
API Gravity @ 60° F	29.5	29	28.5	27.5	26.5
Viscosity Index	95	95	95	95	95
Viscosity:					
cSt @ 100° C	6.7	8.6	11.1	14.5	18.8
cSt @ 40° C	46	68	100	150	220
SUS @ 210° F	48	54	63	76	93
SUS @ 100° F	215	315	465	700	1000
Pour Point, °C (°F)	-28 (-18)	-26 (-15)	-24 (-11)	-22 (-8)	-20 (-4)
Flash Point, °C (°F)	200 (395)	205 (400)	225 (435)	235 (455)	245 (475)
Color, ASTM	1	L1.5	1.5	2.5	3.5