



Green Mineral Gear Lubricant

Green Mineral Gear Lube is a purely mineral-based gear lubricant intended for use in steering gears, universal joints, and low torque industrial gears where API Service designation GL-1 applies. They should be used where the manufacturer recommends the use of an all-mineral or non-additive gear oil.

These products do not contain any extreme pressure additives, although their film strength is ample for their intended service. They are available in SAE grades 90 and 140.

United Green Mineral Gear Lubes are pure gold for your gears.

Beneficial Features:

Benefits of these products include:

- 💧 **Good oxidation**
- 💧 **Low foaming tendencies**
- 💧 **Compatibility with other gear oils**

Application Specifications:

Green Mineral Gear Lubes meet performance requirements of API Service Classification GL-1. GL-1 service is designed for low speed, low torque conditions such as:

- 💧 Heavy-duty manually operated transmission and gear boxes
- 💧 Spiral bevel and worm axles
- 💧 Steering gears, universal joints and spline shafts
- 💧 Enclosed industrial gears and flexible couplings

These lubricants are not recommended for hypoid gears.

Product Containers Available:

Bulk
55 Gallons
30 Gallons
5 Gallon Pails
2/2.5 Gallon

Typical Physical Specifications:

<u>CODE</u>	<u>3239</u>	<u>3231</u>
<u>GRADE</u>	<u>90</u>	<u>140</u>
Pour Point °F	0	+15
Flash Point °F	375	400
Viscosity:		
SUS @ 100 °F	950	3100
SUS @ 210 °F	85	130