



Multi-Purpose Gear Lubricant

United Gear Oils are multipurpose lubricants utilizing premium base stocks in conjunction with additives blended from sulfur and phosphorous to provide a high level of protection against extreme pressure and shear.

United Multi-Purpose Gear Lubricants are available in three viscosity grades; GL-4 80, GL-4 90 GL-4 140. Each maintains viscous properties throughout its usage and will not experience rapid viscosity loss due to shear.

You have a multitude of uses; that's why there are United Multi-Purpose Gear Oils for all of them.

Beneficial Features:

Additional benefits of these gear oils include:

- 💧 **Protection from scuffing**
- 💧 **Anti-weld properties**
- 💧 **Strong defense against wear**

Application Specifications:

United Multi-purpose Gear Oil is recommended for manual transmissions, differentials, final drives and other gearcases of trucks, buses, cars, farm tractors and earth-moving equipment where oils of the GL-4 performance level are required.

The protection offered by United Multi-Purpose Gear Lubricants is strong, but less than that given by United Premium Gear Lubricants, where GL-5 performance is required.

Product Containers Available:

Bulk
55 Gallons
30 Gallons
5 Gallon Pails
2/2.5 Gallon

Typical Physical Specifications:

<u>CODE</u>	<u>3128</u>	<u>3129</u>	<u>3121</u>
<u>GRADE</u>	<u>80</u>	<u>90</u>	<u>140</u>
Gravity API	26.2	25.8	23.4
Pour Pt. °F	-10	0	+15
Flash Point °F	360	380	400
Viscosity:			
SUS @ 100 °F 700	373	940	3100
SUS @ 210 °F 76	56	82	130