

UNITED FULL SYNTHETIC SAE 0W-16 PASSENGER CAR MOTOR OIL



United Full Synthetic SAE 0W-16 Passenger Car Motor Oil is formulated to meet the regulatory and engine durability performance requirements for ILSAC GF-6B, API SP. This includes enhanced fuel efficiency, better oxidation stability, better piston cleanliness & better wear control.

Features:

- Additive technology that you can trust, United Full Synthetic SAE 0W-16 meets the HTHS (High Temp High Shear) viscosity requirements of 2.3-2.6 mPa.s, while ensuring long term protection of the engine.
- Improved fuel economy for consumers as measured by Sequence VIF fuel efficiency test.
- Provides strong protection against low-speed pre-ignition (LSPI), which is a phenomenon that can lead to pre-ignition knock in turbocharged, direct injection gasoline engines.
- Provides improved oxidative stability and low-temperature performance.
- Features a high-quality detergent package for excellent engine cleanliness.
- Provides excellent anti-wear protection of critical engine parts.
- A high level of dispersancy protects against sludge, engine rust, and corrosion.
- Designed for today's gasoline engines that operate at higher temperatures.

TYPICAL SPECIFICATION DATA

United Full Synthetic SAE 0W-16 Passenger Car Motor Oil	
SAE GRADE	0W-16
Viscosity @ 100°C (cSt)	7.7
Viscosity @ 40°C (cSt)	39.6
Viscosity Index	168
Density (lb/gal)	7.043
CCS Viscosity (cP) -35°C	5230
HTHS mPa.s	2.3
Pour Point (°F)	-40
Flash Point (°C)	-54
NOACK Volatility, % evaporation loss	12.3

Meets or Exceeds:

- API SP-RC, ILSAC GF-6B
- Resource Conserving



Product Availability:

- | | |
|-----------|----------------|
| • 55 Gal | • Item# 389602 |
| • 265 Gal | • Item# 389603 |
| • Bulk | • Item# 389606 |