

# UNITED SYNTHETIC PASSENGER CAR MOTOR OIL 10W-30



This API 10W-30 Full-Synthetic gasoline motor oil is formulated to help protect pistons, bearings, cams, timing chains and other engine components against wear, even under the elevated heat and stress. It meets or exceeds the latest and most stringent domestic vehicle performance specifications and is compliant with modern emissions systems.

## Features:

- Delivers superior protection against engine wear
- Helps reduce oil consumption and maximize fuel economy
- Resists heat and oxidation for long oil life
- Optimized detergency helps maintain engine cleanliness
- Compatible with conventional and synthetic engine oils.
- API SQ Resource Conserving, ILSAC GF-7A
- API SN PLUS, SN SM
- Chrysler MS-6395

## TYPICAL SPECIFICATION DATA

Description	Test	SAE Grade 10W-30
Viscosity 100°C, cSt	ASTM D445	10.8
Viscosity 40°C, cSt	ASTM D445	66.3
Viscosity Index	ASTM D2270	153
Cold Crank Simulator, cP	ASTM D5293	3925 (-25)
Color	ASTM D1500	L2.5
Flash Point, °C (°F) (COC)	ASTM D92	228 (442)
Fire Point, °C (°F) (COC)	ASTM D92	254 (489)
Pour Point, °C (°F)	ASTM D97	-40 (-40)
NOACK (% wt loss)	ASTM D5800	4.4%
Total Base Number (TBN)	ASTM D2896	8.0

## Product Availability:

- Offered in pails, drums and totes, contact your local United Lubricants Account Manager for availability.