

# UNITED NON-DETERGENT MOTOR OIL



LUBRICANTS

United Non-Detergent Motor Oil is suitable for older, pre-1964 passenger cars. It may be used as a GL-1 gear oil, hoist oil, or a general machine oil. United Non-Detergent Motor Oil can be used for air compressors and other industrial applications that require a non-detergent motor oil. It is also suitable for lightly loaded gear sets that do not require an extreme-pressure lubricant. Meets API SA service classification.

## Typical Specification Data:

UNITED NON-DETERGENT MOTOR OIL			
SAE GRADE	10W	20W	30
API Gravity @ 60°F	29.5	29	28.5
Viscosity Index	95	95	95
Viscosity: cSt @ 100°C	6.7	8.6	11.1
Viscosity: cSt @ 40°C	46	68	100
Viscosity: SUS @ 210°F	48	54	63
Viscosity: SUS @ 100°F	215	315	465
Pour Point, °C (°F)	-28 (-18)	-26 (-15)	-24 (-11)
Flash Point, °C (°F)	200 (395)	205 (400)	225 (435)
Color, ASTM	1	L1.5	1.5

## Meets or Exceeds:

- API SA (obsolete) performance requirements

## Product Availability: United Non-Detergent Motor Oil SAE 10

- 5 Gal
- 55 Gal
- 265 Gal
- Bulk
- Item # 191287
- Item # 191288
- Item # 210708
- Item # 192623

## Product Availability: United Non-Detergent Motor Oil SAE 20

- 5 Gal
- 55 Gal
- 265 Gal
- Bulk
- Item # 191291
- Item # 192742
- Item # 210710
- Item # 192626

## Product Availability: United Non-Detergent Motor Oil SAE 30

- 5 Gal
- 55 Gal
- 265 Gal
- Bulk
- Item # 191294
- Item # 191295
- Item # 210711
- Item # 191296