

United Synthetic Diesel Engine Oil withstands the stress of heat, soot, and acids to help prevent deposits, wear, and corrosion, outperforming best-in-class conventional SAE 15W-40 oils. United Synthetic Diesel Engine Oil is formulated for use with all modern emissions control systems.

Use United Synthetic Diesel Engine Oil in diesel engines that require any of the specifications listed below.

Specifications	5W-30	10W-30	0W-40	15W-40
ACEA E9, E7	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>		<input checked="" type="checkbox"/>
API CK-4, CJ-4, CI-4+, CF	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>		<input checked="" type="checkbox"/>
Caterpillar ECF-3, ECF-2, ECF-1-a	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
Chrysler MS 10902		<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
Cummins CES20086, CES 20081	<input checked="" type="checkbox"/>		<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
Detroit Diesel DFS 93K222, DDC 93K218, 93K215, 93K214	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
Deutz DQC III-10 LA	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>		<input checked="" type="checkbox"/>
Ford WSS-M2C171-F1	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>		<input checked="" type="checkbox"/>
Jaso DH-2	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
Mack EOS-4.5, EO-O	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>		<input checked="" type="checkbox"/>
MAN 3575	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
MB 228.31	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>		<input checked="" type="checkbox"/>
MTU Type 2.1, Type I & II	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>		<input checked="" type="checkbox"/>
Renault RLD-4, RLD-3	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>		<input checked="" type="checkbox"/>
Volvo VDS-4.5, VDS-4, VDS-3	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>		<input checked="" type="checkbox"/>
ACEA E9, E7	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>

Features and Benefits:

- Enables fleets to capture significant long-term cost efficiencies, while maximizing equipment performance and protection.
- Provides better cold-flow properties than conventional oils for faster startup protection and improved cold-weather efficiency.
- Outstanding wear protection
- Extended drain capable with used oil analysis program
- Improved fuel economy performance over conventional SAE 15W-40 oils
- Exceptional soot dispersancy
- Superior protection against deposit and sludge buildup
- Greatest resistance to thermal and oxidative breakdown
- Advanced additive technology to protect modern emission-control systems
- Long-lasting TBN to neutralize acids and guard against corrosive wear

Description	5W-30	10W-30	0W-40	15W-40
SAE Grade				
Kinematic Viscosity @ 100°C, cSt ASTM D445	12	11.9	15.4	15.4
Kinematic Viscosity @ 40°C, cSt ASTM D445	67.5	79.4	91.6	113.2
Viscosity Index ASTM D2270	177	145	179	142
Cold Crank Simulator, cP ASTM D5293	5739 (-30)	5650 (-25)	5800 (-35)	5050 (-20)
Flash Point °C (°F) (COC) ASTM D92	228 (442)	228 (442)	224 (435)	240 (464)
Pour Point °C (°F) ASTM D97	-43 (-45)	-38 (-36)	-47 (-53)	-38 (-36)
Noack (% wt loss) ASTM D5800	7.1	4.7	11	4.8
Total Base Number (TBN) ASTM D2896	0.47	0.46	0.47	0.46
High-Temperature/High-Shear Viscosity,(cP) ASTM D5481	10	10	10	10
Sulfated Ash, (wt %) ASTM D874	3.6	3.6	4.1	4.6

The typical properties listed above reflect the general characteristics of the product/s and are not manufacturing specifications. Variations that do not affect product performance should be expected. Product formulations are subject to change without notice. The customer or user is responsible for determining the product's suitability for use with their equipment.

Product Availability

Container	5W-30	10W-30	0W-40	5W-40	15W-40
12 x 1 qt.	<input checked="" type="checkbox"/>				
2 x 2.5 Gal.	<input checked="" type="checkbox"/>				