

UNITED SYNTHETIC PASSENGER CAR MOTOR OIL 0W-40



This API 0W-40 Full-Synthetic gasoline motor oil is formulated to provide outstanding anti-wear protection, high-temperature oxidation resistance and excellent cold-flow properties. Meets the latest and most stringent domestic performance specifications, fuel efficiency, and emissions-system compliant.

Features:

- Delivers excellent heat resistance and cold-temperature performance.
- Helps prevent damaging low-speed pre-ignition (LSPI) in turbocharged, direct-injection engines.
- High detergent/dispersant content maintains engine cleanliness. Superior cold-temperature performance for fast startup protection.
- Optimized detergency helps maintain engine cleanliness.
- API SP Resource Conserving, ILSAC GF-6
- API SP, SN PLUS, SN, SM

TYPICAL SPECIFICATION DATA

Description	Test	SAE Grade 0W-40
Viscosity 100°C, cSt	ASTM D445	15.2
Viscosity 40°C, cSt	ASTM D445	87.2
Viscosity Index	ASTM D2270	184
Cold Crank Simulator, cP	ASTM D5293	5119 (-35)
Color	ASTM D1500	L3.5
Flash Point, °C (°F) (COC)	ASTM D92	228 (442)
Fire Point, °C (°F) (COC)	ASTM D92	244 (471)
Pour Point, °C (°F)	ASTM D97	-50 (-58)
NOACK (% wt loss)	ASTM D5800	10.9%
Total Base Number (TBN)	ASTM D2896	8.0

Product Availability:

- Offered in pails and drums, contact your local United Lubricants Account Manager for availability.