# UNITED BLUE MAX SYNTHETIC BLEND GREASE



United Blue Max Synthetic Blend Grease is made for a wide range of lubrication demands, thus reducing the need to carry large grease inventories. In addition, this grease provides excellent adhesive characteristics for stay-in-place performance and exceptional resistance to water and other adverse conditions. Its balanced, high load-carrying ability provides maximum protection by reducing friction and wear.

#### Storage and Handling:

- Tube should always be stored upright.
- If grease is left in gun: Depressurize, wipe clean, and store in clean, cool, dry place.
- Avoid prolonged storage, inspect if more than one year old.
- Storage life up to five years.
- Store in cool, dry indoor area that does not exceed 86°F and remains above 32°F.
- Do not store near heat source or expose to direct sunlight.
- Store in original packaging or container and keep container closed until time of use.
- Wipe lid or cover clean before opening.
- Always use clean tools and dispensing equipment.
- Close or cover container after use.

#### Features:

- Provides excellent bearing migration to ensure quick and thorough grease contact
- Good adhesion to metal during wet conditions
- Strong load-carrying capabilities and exceeds GC-LB specifications
- Best choice for inventory consolidation
- Environmentally conscious, contains no heavy metals

#### **Applications:**

- Heavy-duty truck fleets
- Automotive fleets
- Construction
- Agriculture
- Industrial

# **TYPICAL SPECIFICATION DATA**

UNITED BLUE MAX SYNTHETIC BLEND GREASE	
NLGI GRADE	2
Thickener Type	Lithium Complex
Texture	Smooth
Color	Blue
Penetration 60 Strokes	265-295
Dropping Point (°F)	>500
Copper Corrosion	1B
Timken OK Load (lbs.)	50
4-Ball Ep Performance Weld Point (kg)	500
4-Ball Wear Scar (mm)	0.6
Copper Corrosion	1B
Base Oil Viscosity @ 100°C (cSt)	5.8
Base Oil Viscosity @ 40°C (cSt)	38.0
Base Oil Viscosity Index	90

### **Recommended for Use in the Following Specifications:**

• Meets NLGI GC/LB specifications

## **Product Availability:**

- 30 x 14-oz tubes
- 35-lb pail
- 120-lb keg
- 400-lb drum

- Item # 325370
- Item # 191549
- Item # 191548
- Item # 191551