

UNITED EXTENDED LIFE NOAT COOLANT/ANTIFREEZE PREMIX



United Extended Life NOAT 50/50 Pre-Diluted Coolant/Antifreeze is a 50/50 mix of United Extended Life NOAT Coolant and deionized water. This coolant should be used when topping off cooling systems filled with Extended Life Coolant to ensure proper inhibitor levels are maintained. United Extended Life 50/50 Pre-Diluted NOAT Coolant/Antifreeze is formulated to meet the requirements of today's heavy-duty engines and features a carboxylate base formulation, with nitrite and molybdate that has been used in the marketplace since the mid-1990s.

United Extended Life NOAT 50/50 Pre-Diluted Coolant/Antifreeze is designed to provide effective long-term wet-sleeve liner cavitation and corrosion protection of cooling system components.

Features:

- Delivers cooling system protection for service life with the addition of an extender at half-life:
 - Over-the-road protection: 1,000,000 miles or 8 years
 - Off-road protection: 20,000 hours or 8 years
- Eliminates the need for supplemental coolant additives (SCAs), chemically charged filters, and corrosion-inhibitor testing
- Excellent hot surface aluminum protection
- Outstanding protection in high operating temperatures
- Non-abrasive formula can improve water pump seal life
- Optimal hard water compatibility and reduced hard water scale

TYPICAL SPECIFICATION DATA

UNITED EXTENDED LIFE NOAT COOLANT/ANTIFREEZE PREMIX	
Specific Gravity @ 60°F	1.07
Freezing Point, 50% vol (°F)	-34
Boiling Point, 50% vol (°F)	325
Foaming Test	100 mL/3 sec
pH, 50% vol	8.8
Color	Red



Meets or Exceeds:

- ASTM D3306
- ASTM D4340
- ASTM D6210
- CAT EC-1
- Case New Holland MAT 3620
- Cummins 14439
- Ford ESE-M97B18-C
- John Deere H24A
- Navistar MPAPS B-1 Type III
- Perkins (CAT) SEBU7833-03
- TMC RP 329B
- Volvo 20774185

Product Availability:

- 55 Gal
- 265 Gal
- Bulk
- Item # 330430
- Item # 330429
- Item # 330428