

United HD Gear Synthetic SAE 75W-90 is an extreme-pressure, full synthetic, heavy-duty gear lubricant for use in moderate to severe service applications. Outperforms conventional gear oils in GL-5 applications, including:

- Heavy duty
- Construction
- Agriculture
- Industrial

## Features:

---

- Excellent protection of heavily loaded gears during long drain intervals
- Resistance to thermal degradation
- High viscosity index
- Excellent sear stability
- Reduces leaks and extends seal life
- Protects against rust and oxidation
- Excellent low-temperature properties
- Anti-foam protection

# TYPICAL SPECIFICATION DATA

UNITED HD GEAR SYNTHETIC SAE 75W-90	
SAE Grade	75W-90
Viscosity @ 100°C (cSt)	16.0
Viscosity @ 40°C (cSt)	108.1
Viscosity Index	159
Density (lb/gal)	7.22
Pour Point (°C)	-36
Pour Point (°F)	-33
Flash Point (°C)	215
Flash Point (°F)	419

## Meets or Exceeds:

- API GL-5
- API MT-1
- Arvin Meritor 0-76N, Q&R
- Eaton (GL-5/MT-1)
- Mack GO-J
- PG-2 LS

## Product Availability:

- 2 x 2.5 Gal\*
- 16 Gal
- 30 Gal
- 55 Gal
- 265 Gal
- Item # 277220
- Item # 277218
- Item # 277219
- Item # 281325

*\*Contact your local United Account Manager for product availability.*