

UNITED PREMIUM NATURAL GAS FLEET SAE 15W-40



United Premium Natural Gas Fleet SAE 15W-40 is formulated with high-quality base oil and a unique additive package designed specifically for compressed natural gas (CNG) engine applications. United Premium Natural Gas Fleet SAE 15W-40 is specially formulated to perform and protect at the higher combustion temperatures present in CNG engines by minimizing oxidation and reducing nitration.

United Premium Natural Gas Fleet SAE 15W-40 also contains special detergents designed to provide the optimum balance of acid neutralization while keeping valves free of deposits.

TYPICAL SPECIFICATION DATA

UNITED PREMIUM NATURAL GAS FLEET SAE 15W-40	
SAE GRADE	15W-40
Viscosity @ 100°C (cSt)	15.8
Viscosity @ 40°C (cSt)	123.2
Viscosity Index	136
Density (lb/gal)	7.28
CCS Viscosity (cP)	6,500
Pour Point (°C)	-33
Pour Point (°F)	-27
Flash Point (°C)	236
Flash Point (°F)	457
TBN	10.5
Sulfated Ash, wt%	0.5

Meets or Exceeds:

- Meets Cummins CES 20074

Product Availability:

- 55 Gal
- 265 Gal
- Bulk
- Item # 277025
- Item # 309730
- Item # 277023