

UNITED MULTI TRANS III AUTOMATIC TRANSMISSION FLUID (ATF)



United Multi Trans III Automatic Transmission Fluid is approved for use in all automatic transmissions that specify either a General Motors DEXRON®-III or Ford MERCON® fluid. Manufactured from high-quality base oils and specially selected additives, United Multi Trans III ATF has excellent oxidation stability and low-temperature properties and helps minimize the formation of gum, sludge, lacquer, and varnish. It provides excellent protection from rust, corrosion, and wear.

United Multi Trans III ATF meets the requirements for GM DEXRON-III H Revision specification and may be used in previous applications requiring a DEXRON fluid. It can be used for mobile hydraulic and some industrial applications that operate over a wide variety of automatic transmissions and in industrial anti-wear hydraulic systems. United Multi Trans III ATF meets the requirements for Allison C-4, Caterpillar TO-2, and Sundstrand Hydrostatic transmissions.

Features:

- Protects metal parts from corrosion
- Provides excellent oxidative stability under severe conditions
- Reduces sludge and varnish buildup
- Protects transmission gears and allows them to operate smoothly
- Maintains lubricity
- Flows well for cold startup
- Provides excellent shift feel with no shudder
- Prevents fluid breakdown at higher operating temperatures
- Long fluid life and long transmission life
- Compatible with common transmission seal material

Recommended Use:

United Multi Trans III ATF is suitable for use in powershift transmissions, torque converters, hydrostatic transmissions, and applications such as air compressors, hydraulic pumps, power steering boxes, and other types of service where an ATF is recommended. Always check the owner's manual for proper recommendations.

United Multi Trans III Automatic Transmission Fluid is recommended for use in automatic transmissions manufactured by General Motors and Ford for model years 2006 and prior (except those calling for FORD type "F" fluid, Mercon SP, Mercon V, DEXRON VI, DCT, and CVT fluids).

TYPICAL SPECIFICATION DATA

UNITED MULTI TRANS III ATF	
Viscosity @ 100°C (cSt)	7.4
Viscosity @ 40°C (cSt)	36.5
Viscosity Index	174
Density (lb/gal)	7.13
CCS Viscosity (cP)	3,600
Pour Point (°C)	-45
Pour Point (°F)	-49
Flash Point (°C)	222
Flash Point (°F)	432
Sulfated Ash, wt%	0.0

Meets or Exceeds:

- Allison C-3, C-4
- AMC/Jeep/Eagle
- Chrysler MS-7176 (top-off only)
- Ford M2C138-CJ
- Ford M2C166-H
- Ford MERCON
- GM DEXRON-III H, DEXRON-II
- Hydraulic systems:
 - Cincinnati Milacron
 - Hagglunds-Denison HF-0, HF-1, HF-2
 - Sperry Vickers I-286-S, M-2950-S, 35VQ25
 - Sundstrand Hydraulics

Product Availability:

- 12 x 1 Qt
- 2 x 2.5 Gal
- 30 Gal
- 55 Gal
- 265 Gal
- Item # 191279
- Item # 191280
- Item # 191281
- Item # 191283
- Item # 210930