

United Proform Concrete Release Oil is formulated with a specific blend of fatty acids and high-quality base oils for optimal release of forms from concrete and prevents buildup of concrete on wood and metal forms. United Proform Concrete Release Oil is a ready-to-use product and does not require dilution. This release fluid may be applied easily, using spraying or brush. For best results, it should be applied to clean, dirt-free surfaces.

## Features/Benefits:

- Excellent surface finish, smooth release and even spreading of the oil on wood or steel forms.
- Designed to protect and extend the life of wood forms.
- Repels water to reduce the formation of corrosion on metal forms.
- Recommended for use in the manufacture of precast concrete panels.
- Prevents staining, build-up, and corrosion of forms.
- Contains a low odor release agent and is light colored.

## TYPICAL SPECIFICATION DATA

UNITED PROFORM CONCRETE RELEASE OIL		
ISO GRADE		10
Viscosity @ 100°C (cSt)	ASTM D445	3.0
Viscosity @ 40°C (cSt)	ASTM D445	12.0
Viscosity Index	ASTM D2270	95
Pour Point °F, °C	ASTM D97	-11.2 °F -24° C
Color	ASTM D1500	L0.5
Density, lbs./gal. @ 60°F		7.069

## Product Availability:

- 5 Gal. Pail
- 55-gal. Drum
- 265-gal. Totes
- Bulk
- Item #345396
- Item #227011
- Item #227012
- Item #227010