

United Synthetic HD Commercial Automatic Transmission Fluid (ATF) is a premium-quality synthetic lubricant formulated with a high-quality detergent and viscosity modifier additive package and is suitable for use in most heavy-duty transmission applications. United Synthetic HD Commercial ATF is formulated with the quality level to support extended drain intervals, where applicable.

Features:

- Excellent thermal and oxidative stability for long transmission life
- Exceptional all-weather performance in both hot and cold temperature extremes
- Durable friction properties ensure smoother-shifting transmissions
- Shear stable for long-term viscosity protection

TYPICAL SPECIFICATION DATA

UNITED SYNTHETIC HD COMMERCIAL ATF	
Viscosity @ 100°C (cSt)	7.4
Viscosity @ 40°C (cSt)	34.5
Viscosity Index	189
Density (lb/gal)	7.05
Pour Point (°C)	-48
Pour Point (°F)	-54
Flash Point (°C)	216
Flash Point (°F)	421

Meets or Exceeds:

- Allison C-4
- MAN 339 Type V1, Z2
- Voith G 607
- ZF TE-ML 14B

Product Availability:

- 5 Gal
- 55 Gal
- 275 Gal
- Bulk
- Item # 258943
- Item # 258942
- Item # 258944
- Item # 258941