

UNITED SYNTHETIC RECIPROCATING AIR COMPRESSOR OIL ISO 100



United Synthetic Reciprocating Air Compressor Oil ISO 100 is a full synthetic, nondetergent compressor oil, formulated to protect against wear and varnish in reciprocating air compressors. Oil life is dependent on operating conditions and maintenance practices—a regular oil analysis program is recommended.

Features:

- Anti-wear fortified and designed to control foam for improved film strength and wear protection.
- Excellent resistance to varnish and carbon deposits helps keep valves clean and long-lasting.
- Separates from water, allowing for easy removal and disposal.
- Compatible with conventional compressor oils.

TYPICAL SPECIFICATION DATA

UNITED SYNTHETIC RECIPROCATING AIR COMPRESSOR OIL ISO 100	
ISO GRADE	100
Viscosity @ 100°C (cSt)	13.4
Viscosity @ 40°C (cSt)	101.1
Viscosity Index	131
Pour Point (°C)	-38
Pour Point (°F)	-36
Flash Point (°C)	256
Flash Point (°F)	493
Copper Corrosion	1A
4-Ball Wear Scar (mm)	0.45

Product Availability:

- 5 Gal*
- 55 Gal*
- 275 Gal*

**Contact your local United Account Manager for product availability.*