

United Timber Pro Bar & Chain Oil is designed for use in all types of chain saws using either manual or automatic chain oiling systems. This product is manufactured from high-performing base oil and additives to reduce wear and sling-off and to provide effective lubrication. It may also be used to lubricate chain drives in a variety of other applications, including farm machinery, lawn and garden, and industrial equipment.

Features:

- Anti-wear protection for chain, bar, and sprocket life
- Reduced downtime for chain adjustments
- Tackiness additives to reduce oil sling-off during use, resulting in better chain performance and less oil usage

TYPICAL SPECIFICATION DATA

UNITED TIMBER PRO BAR & CHAIN			
SAE GRADE	30	90	140
Viscosity @ 100°C (cSt)	10.5	19.5	34.0
Viscosity @ 40°C (cSt)	67.0	196.0	509.0
Viscosity Index	145	114	101
Density (lb/gal)	7.21	7.39	7.52
Pour Point (°C)	-36	-9	-6
Pour Point (°F)	-33	16	21
Flash Point (°C)	214	250	250
Flash Point (°F)	417	482	482



Product Availability: United Timber Pro Bar & Chain SAE 30

- 55 Gal
- 265 Gal
- Bulk
- Item # 195593
- Item # 210946
- Item # 195592

Product Availability: United Timber Pro Bar & Chain SAE 90

- 55 Gal
- 265 Gal
- Bulk
- Item # 192372
- Item # 210947
- Item # 192371

Product Availability: United Timber Pro Bar & Chain SAE 140

- 55 Gal
- 265 Gal
- Bulk
- Item # 192368
- Item # 210942
- Item # 192367